

Tabel specificatii FTXC-E

				FTXC20EV1B	FTXC25EV1B	FTXC35EV1B	FTXC50EV1B	FTXC60EV1B	FTXC71EV1B
Power input	Cooling	Nom.	kW	0.595	0.765	1.045	1.55	1.89	2.38
	Heating	Nom.	kW	0.67	0.75	1.07	1.515	1.68	2.46
Casing	Colour			White	White	White	White	White	White
	Material			High impact polystyrene	High impact polystyrene	High impact polystyrene	High impact polystyrene	High impact polystyrene	High impact polystyrene
Dimensions	Unit	Height	mm	288	288	288	288	297	297
		Width	mm	770	770	770	770	990	990
		Depth	mm	234	234	234	234	273	273
Weight	Unit		kg	9.0	9.0	9.5	9.5	13.0	13.0
Fan	Air flow rate	Cooling	High	m ³ /min	10.8	10.8	11.1	12.5	20.4
			Medium	m ³ /min	8.1	8.1	8.7	9.9	14.5
			Low	m ³ /min	6.1	6.1	6.4	8.1	12.5

			Silent operation	m³/min	5.4	5.4	5.4	7.4	10.2	10.2
Sound power level	Cooling			dBA	57	57	58	60	63	63
Sound pressure level	Cooling	High	dBA	40	40	41	47	48	48	48
		Medium	dBA	33	33	34	39	42	42	42
		Low	dBA	26	26	26	33	38	38	38
		Silent operation	dBA	21	21	22	30	31	31	31
Piping connections	Liquid	OD	mm	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas	OD	mm	9.52	9.52	9.52	12.7	12.7	12.7	12.7
	Drain				16.5	16.5	16.5	16.5	16.5	16.5
Control systems	Infrared remote control				ARC486A6	ARC486A6	ARC486A6	ARC486A6	ARC486A6	ARC486A6
Power supply	Name				V1	V1	V1	V1	V1	V1
	Phase				1~	1~	1~	1~	1~	1~

	Frequency	Hz	50	50	50	50	50	50
	Voltage	V	220-240	220-240	220-240	220-240	220-240	220-240