Klima House

Tabel cu specificatiile tehnice ERLA11-14DV3

				ERLA11DAV3	ERLA11D2V3	ERLA14DAV3	ERLA14D2V3
Dimensions	Unit	Height	mm	870	870	870	870
		Width	mm	1,100	1,100	1,100	1,100
		Depth	mm	460	460	460	460
Weight	Unit		kg	101	101	101	101
Fan	Air flow rate Heating	High	m³/min	55.8	55.8	70.4	70.4
	Cooling	High	m³/min	70.4	70.4	85.0	85.0
Operation range	Cooling	Min.	°CDB	10	10	10	10
		Max.	°CDB	43	43	43	43
	Domestic hot water	Max.	°CDB	25 (1), 35 (1)	25 (1), 35 (1)	25 (1), 35 (1)	25 (1), 35 (1)
		Min.	°CDB	-25	-25	-25	-25
Piping connections	Liquid	OD	mm	9.50	9.50	9.50	9.50
	Gas	OD	mm	15.9	15.9	15.9	15.9
	Drain	OD	mm	26	26	26	26
	Level difference IU - OU	Max.	m	30.0	30.0	30.0	30.0
	Heat insulation			Both liquid and gas pipes			
Sound power level	Heating	Nom.	dBA	62.0 (2)	62.0 (2)	62.0 (2)	62.0 (2)
Sound pressure evel	Heating	Nom.	dBA	48.0 (2)	48.0 (2)	48.0 (2)	48.0 (2)
Refrigerant	Туре			R-32	R-32	R-32	R-32
	GWP			675.0	675.0	675.0	675.0
	Charge kg		3.80	3.80	3.80	3.80	
Power supply	Name			V3	V3	V3	V3
	Phase			1~	1~	1~	1~
	Frequency Hz			50	50	50	50
	Voltage		V	230	230	230	230

Current	Recommended fuses	А	32	32	32	32
Notes			(1) - For more details, see operation range drawing	(1) - For more details, see operation range drawing		(1) - For more details, see operation range drawing
			(2) - Measured with a pressure drop of 10 kPa in the heating system at an operating	drop of 10 kPa in the heating		(2) - Measured with a pressure drop of 10 kPa in the heating system at an operating condition
			condition of leaving water 47-	of leaving water 47-55°C in a room		of leaving water 47-55°C in a room