

Tabel cu specificatiile tehnice pentru ERGA04-08EVA

				ERGA04EAV3A	ERGA06EAV3A	ERGA08EAV3A
Dimensions	Unit	Height	mm	740	740	740
		Width	mm	884	884	884
		Depth	mm	388	388	388
Weight	Unit		kg	58.5	58.5	58.5
Operation range	Cooling	Min.	°CDB	10	10	10
		Max.	°CDB	43	43	43
	Domestic hot water	Max.	°CDB	35	35	35
		Min.	°CDB	-25	-25	-25
Piping connections	Liquid		OD mm	6	6	6
	Gas		OD mm	15.9	15.9	15.9
	Drain		OD mm	18	18	18
	Level difference	IU - OU	Max. m	20.0	20.0	20.0
	Heat insulation			Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Sound power level	Heating		Nom. dBA	58 (1)	60 (1)	62 (1)
	Cooling		Nom. dBA	61 (1)	62 (1)	62 (1)
Sound pressure level	Heating		Nom. dBA	44 (1)	47 (1)	49 (1)
	Cooling		Nom. dBA	48 (1)	49 (1)	50 (1)
Refrigerant	Type			R-32	R-32	R-32
	GWP			675.0	675.0	675.0
	Charge		kg	1.50	1.50	1.50
Power supply	Name			V3	V3	V3
	Phase			1N~	1N~	1N~
	Frequency			50	50	50

	Voltage	V	230	230	230
Current	Recommended fuses	A	16	16	16
Notes			(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)	(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)	(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)