Klima House

Tabel cu specificatiile tehnice ERLA11-14DW1

				ERLA11DAW1	ERLA11D2W1	ERLA14DAW1	ERLA14D2W1
Sound pressure level	Heating	Nom.	dBA	48.0 (2)	48.0 (2)	48.0 (2)	48.0 (2)
Sound power level	Heating	Nom.	dBA	62.0 (2)	62.0 (2)	62.0 (2)	62.0 (2)
Refrigerant	GWP			675.0	675.0	675.0	675.0
	Charge		kg	3.80	3.80	3.80	3.80
	Туре			R-32	R-32	R-32	R-32
Dimensions	Unit Width		mm	1,100	1,100	1,100	1,100
		Depth	mm	460	460	460	460
		Heigh	tmm	870	870	870	870
Weight	Unit		kg	101	101	101	101
Operation range	Cooling	Max.	°CDB	43	43	43	43
		Min.	°CDB	10	10	10	10
	Domestic hot water Min.		°CDB	-25	-25	-25	-25
		Max.	°CDB	25 (1), 35 (1)	25 (1), 35 (1)	25 (1), 35 (1)	25 (1), 35 (1)
Fan	Air flow rate Heating High		m³/min	55.8	55.8	70.4	70.4
			m³/min	70.4	70.4	85.0	85.0
Piping connections	Heat insulation			Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
	Liquid OD		mm	9.50	9.50	9.50	9.50
	Gas OD		mm	15.9	15.9	15.9	15.9
	Drain OD		mm	26	26	26	26
	Level difference	IU - OU Max.	m	30.0	30.0	30.0	30.0
Power supply	Phase			3~	3~	3~	3~
11, 5	Name			W1	W1	W1	W1
	Frequency Hz		Hz	50	50	50	50
	Voltage		V	400	400	400	400
Current	Recommen	ded fuses	Α	16	16	16	16
Notes				(1) - For more details, see operation range drawing	(1) - For more details, see operation range drawing	(1) - For more details, see operation range drawing	(1) - For more details, see operation range drawing
				(2) - Measured with a pressure drop of 10 kPa in the heating	(2) - Measured with a pressure drop	(2) - Measured with a pressure drop of 10 kPa in the heating system at an	(2) - Measured with a pressure drop of 10 kPa in the heating system at an

leaving water 47-55°C in a room	47-55°C in a room with an ambient	47-55°C in a room with an ambient of	47-55°C in a room with an ambient
with an ambient of 20°C. DB/WB	of 20°C. DB/WB 7°C/6°.	20°C. DB/WB 7°C/6°.	of 20°C. DB/WB 7°C/6°.
7°C/6°.			