

Tabel cu specificatiile tehnice pentru EBSH-D

					EBSH11P30DF	EBSH11P50DF	EBSH16P50DF	EBSH16P30DF
Sound pressure level	Nom.			dBA	36.8	36.8	40.3	40.3
Refrigerant	GWP				675.0	675.0	675.0	675.0
	Charge			kg	3.80	3.80	3.80	3.80
	Type				R-32	R-32	R-32	R-32
Operation range	Cooling	Ambient	Min.	°CDB	0 (2)	0 (2)	0 (2)	0 (2)
		Water side	Max.	°C	0 (2)	0 (2)	0 (2)	0 (2)
			Min.	°C	0 (2)	0 (2)	0 (2)	0 (2)
	Heating	Water side	Max.	°C	0 (2)	0 (2)	0 (2)	0 (2)
			Min.	°C	0 (2)	0 (2)	0 (2)	0 (2)
Sound power level	Nom.			dBA	44.7	44.7	49.0	49.0
Dimensions	Unit		Width	mm	594	792	792	594
			Depth	mm	680	817	817	680
			Height	mm	1,893	1,910	1,910	1,893
Casing	Material				Impact resistant polypropylene	Impact resistant polypropylene	Impact resistant polypropylene	Impact resistant polypropylene
	Colour				Traffic white (RAL9016) / Traffic black (RAL9017)	Traffic white (RAL9016) / Traffic black (RAL9017)	Traffic white (RAL9016) / Traffic black (RAL9017)	Traffic white (RAL9016) / Traffic black (RAL9017)
Weight	Unit			kg	93	114	114	93
PED	Category				Category II	Category II	Category II	Category II
Power supply	Phase				1~	1~	1~	1~
	Frequency			Hz	50	50	50	50
	Voltage			V	230	230	230	230
Notes					(1) - Heatloss according to EN12897	(1) - Heatloss according to EN12897	(1) - Heatloss according to EN12897	(1) - Heatloss according to EN12897
					(2) - Refer to drawing operation limits	(2) - Refer to drawing operation limits	(2) - Refer to drawing operation limits	(2) - Refer to drawing operation limits